







REACH & RoHS
COMPLIANT



MATERIAL:

HOUSING: LCP,UL94V-0,BLACK.
TERMINAL: PHOSPHOR BRONZE T=0.30MM, C5191, AU BRIGHT TIN
100U NI 50U" G/FU" GOLD PLATING ON CONTACT AREA
SHIELD: C2680,T=0.20MM,20 MIN NICKEL PLATING ON ALL AREA.
GROUNDING STRIP:C2680,T=0.35,NI 50U "BRIGHT TIN 100U"

MACHANICAL:



DURABILITY: 750 CYCLES MIN.
MATING/UNMATING FORC: 2.24 KG.F MAX.
OPERATING TEMPERATURE: -40°C~+85°C.
STORAGE TEMPERATURE: -40°C~+85°C.
ALL CRITICAL DIMENSIONS WITH "±"

ELECTRICAL:

VOLTAGE: 125 VOLTS AC.
CURRENT RATING : 1.5AMP.
DIELECTRIC STRENGTH: 500 VDC RMS 50HZ ,1MIN.
INSULATION RESISTANCE: 500 MEGA OHMS MIN. INITIAL
AFTER 100V DC FOR 1 MINUTE.
CONTACT RESISTANCE: 40 MILLIOHMS MAX.

LED Specification

Standard LED Color	LED Wavelength	Foward(A)	Foward(V)
Green	568nm	20mA	1.85-2.45V
Yellow	585nm	20mA	1.7-2.2V



VOOHU 苏州沃虎电子科技有限公司
Su Zhou Voohu Electronic Tech.Co.Ltd

TITLE:
RJ45 1X1 8P8C SMT

PART NO.:
SYT52D1188AB1A6SB1075

REMARK:


SIZE
A4

SACLE
1:1

SHEET
1/1

UNITS
MM[INCH]

REV
A0



GENERAL TOLERANCES
UNLESS SPECIFIED

x±0.35	x°±3.0°
.x±0.30	.x°±2.0°
.xx±0.25	.xx°±1.5°
.xxx±0.10	.xxx°±1.0°

APPROVED BY:
Geoffrey.Song

CHECKED BY:
Elvis.Song

DESIGND BY:
Sunny.Xu

TEL: +86 400 1048 018

WEB: WWW.WOHU-TEK.COM